



CM 5377

Product Features :

- Low power
- High definition and true reduction the view
- High quality and stable performance
- Mini tube IR waterproof camera
- Daimeter 36, 5 LED internal, IR View distance 30m

Specifications :

Pick-up Device :	1/3" SHARP CCD
System Signal	NTSC/PAL
Number of Pixels :	NTSC : 512(H) * 492(V)
Scanning System :	NTSC : 525 Lines, 60 Field/sec PAL: 625 Lines 50 Fied/Sec
Sync. System :	Internal Sysnchronization
Horizontal resolution :	420TV Lines
GammaCharacteristic :	0.45
Video Output :	1.0 Vp-p 75 Ohm
S/N Ratio :	>=48db(AGC Off)
Electronic Shutter :	NTSC : 1/60 - 100,000 Sec PAL : 1/50 - 100,000 Sec
Operation Temperature :	-10C - +50C Rh95% Max
Storage Temperature :	-20C - +60C Rh95% Max
Cable :	BNC/DC JACK
Gain Control :	Auto
Lens	6mm (Option)
White Balance :	Auto
Minimum illumination	0 Lux (IR ON)
BLC :	Auto
Power Supply	DC 12V +- 10%
Dimensions :	140(L)*60(D) mm
Weight	500g